

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - ADHESIVE
 Date-Revised : 08/10/2017
 Revision No : 2

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: PACER ZAP IT 4 GR (12) - ADHESIVE

MANUFACTURER

Pacer Technology
 3281 E. Guasti Rd., Suite 260
 Ontario, CA 91761

Emergency Contact: CHEMTREC

Emergency Phone: 800-424-9300

Alternate Emergency Phone: 703-527-3887

Product Stewardship: 909-987-0550

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Physical:**

Flammable Liquids, Category 4

GHS LABEL ELEMENTS

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H227: Combustible liquid.

PRECAUTIONARY STATEMENT(S)**Prevention:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P370: In case of fire: Use dry chemical extinguisher or flush with large amounts of water to extinguish.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED: Bonds skin and eyes instantly. Do not get in eyes, in mouth or on skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
2-Methoxyethyl 2-cyanoacrylate	≤ 85 - 100	27816-23-5
Hydroquinone	< 0.01 - 0.1	123-31-9

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - ADHESIVE
 Date-Revised : 08/10/2017
 Revision No : 2

4. FIRST AID MEASURES

EYES: Immediately flush eyes with large quantities of water for several minutes, while holding eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get medical attention if irritation or bonding occurs.

SKIN: Flush skin with water for several minutes. If bonded, immerse bonded areas in warm, soapy water for several minutes. Peel or roll skin or bonded material apart. Get medical attention if irritation occurs. Remove and launder clothing before re-use.

INGESTION: Flush lips with warm water to release lips if bonded. Ingestion is unlikely, though the product may stick in the mouth. Over a period 1-2 days, the product will be loosened by saliva. Avoid swallowing the product. Get medical attention if symptoms occur.

INHALATION: Remove victim to fresh air. Get medical attention if symptoms of exposure persist.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Bonds eyelids immediately.

SKIN: Bonds skin immediately.

SKIN ABSORPTION: Large quantities may react with skin and cause skin burns.

INGESTION: May be harmful if swallowed.

ADDITIONAL INFORMATION: Immediate medical attention should not be required.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: Combustible liquid and vapor. Contact with water will cause the product to polymerize and become solid. Combustion will produce oxides of carbon and nitrogen, and other toxic or irritating compounds.

EXTINGUISHING MEDIA: Use dry chemical extinguisher or flush with large amounts of water.

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

FIRE FIGHTING EQUIPMENT: Wear an approved, positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide/dioxide.

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid releases to the environment. Report spills and releases as required to appropriate authorities.

LAND SPILL: Avoid releases to the environment. Report spills and releases as required to appropriate authorities.

AIR SPILL: Avoid releases to the environment. Report spills and releases as required to appropriate authorities.

GENERAL PROCEDURES: Evacuate spill area and keep unprotected personnel away. Remove all ignition sources such as open flames, etc. Avoid contact with eyes, skin or clothing. Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles, and respirator if needed. Avoid breathing mists or vapors. Ventilate area.

RELEASE NOTES: Collect material with absorbent rags (not paper towels) or wash the material down with water to solidify and scrape off surface. Rinse spill area with water.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid breathing mists or vapors. Use with adequate ventilation.

HANDLING: Avoid contact with the eyes, skin, and clothing. Wear appropriate protective clothing as described in section 8. Wash

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - ADHESIVE
 Date-Revised : 08/10/2017
 Revision No : 2

thoroughly after handling. Keep away from flames and sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use.

STORAGE: Store in a container in a cool, dry, well-ventilated location away from heat, sunlight and incompatible materials. Keep in original container. Prevent moisture contact. Keep container tightly closed when not in use.

STORAGE TEMPERATURE: 2°C (35.6°F) Minimum to 8°C (46.4°F) Maximum

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m ³
2-Methoxyethyl 2-cyanoacrylate	Supplier OEL	TWA	0.2	
	ACGIH TLV	TLV (DSEN)		1
Hydroquinone	OSHA PEL	TWA		2

ENGINEERING CONTROLS: Use with adequate general or local exhaust ventilation to minimize exposure levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical safety goggles are recommended where splashing is possible.

SKIN: Impervious gloves such as nitrile gloves are suggested to prevent skin contact. Do not use PVC, Nylon, or cotton materials. Contact your glove supplier for selection assistance.

RESPIRATORY: If needed, an approved respirator with organic vapor cartridges may be used. For higher exposures, a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form, and concentration. Follow applicable regulations and good Industrial Hygiene practice.

OTHER USE PRECAUTIONS: Impervious clothing is required to prevent skin contact and contamination of personal clothing. An eye wash facility and safety shower should be available in the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Odorless

ODOR THRESHOLD: No data available

APPEARANCE: Transparent liquid

COLOR: Yellow to light green.

pH: No data available

PERCENT VOLATILE: No data available

FLASHPOINT AND METHOD: 80°C (176°F) to 93.3°C (199.94°F)

FLAMMABLE LIMITS: No data available

AUTOIGNITION TEMPERATURE: No data available

VAPOR PRESSURE: No data available

VAPOR DENSITY: No data available

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - ADHESIVE
 Date-Revised : 08/10/2017
 Revision No : 2

BOILING POINT: 74°C (165.2°F) to 76°C (168.8°F)
FREEZING POINT: No data available
MELTING POINT: No data available
POUR POINT: No data available
THERMAL DECOMPOSITION: No data available
SOLUBILITY IN WATER: Polymerizes in presence of water
PARTITION COEFFICIENT: N-OCTANOL/WATER: No data available
EVAPORATION RATE: No data available
DENSITY: No data available
SPECIFIC GRAVITY: 1.19
VISCOSITY #1: 180 to 220 at 25°C (77 °F)
MOLECULAR WEIGHT: No data available
(VOC): < 3 %

10. STABILITY AND REACTIVITY

REACTIVITY: Rapid exothermic polymerization will occur in presence of incompatible materials.
HAZARDOUS POLYMERIZATION: Polymerization will occur on contact with water, amines, alkali, and alcohols. The polymerization is an exothermic reaction and may cause thermal burns.
STABILITY: Stable under normal storage and handling conditions.
CONDITIONS TO AVOID: Keep away from heat, flames, and other sources of ignition. Keep dry. Avoid high humidity or high temperatures above 80C/176F.
POSSIBILITY OF HAZARDOUS REACTIONS: Possible polymerization reaction in the presence of water, amines, alkalis and alcohols.
HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition will produce oxides of carbon and nitrogen, and other toxic or irritating compounds.
INCOMPATIBLE MATERIALS: Water, alcohol, amines, and alkaline materials.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)
2-Methoxyethyl 2-cyanoacrylate	> 5000 mg/kg	> 2000 mg/kg
Hydroquinone	367.3 mg/kg	> 2000 mg/kg

RESPIRATORY OR SKIN SENSITISATION: No data available for the mixture. Testing for skin sensitization is technically not feasible. The adhesive bonds instantaneous to the surface of the skin and polymerizes. The polymerized material is not able to penetrate into the epidermis.

GERM CELL MUTAGENICITY: Hydroquinone: Positive with metabolic activation and negative without metabolic activation in an In-vitro mammalian chromosome aberration test. Positive in mammalian germ cell cytogenetic assay.

CARCINOGENICITY

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - ADHESIVE
 Date-Revised : 08/10/2017
 Revision No : 2

IARC: None known

NTP: None known

OSHA: None known

NOTES: Hydroquinone is classified as a category 2 carcinogen by the EU CLP. None of the other components of this product are listed as carcinogen or suspected carcinogen by IARC, NTP, ACGIH, OSHA, or the EU CLP.

REPRODUCTIVE TOXICITY: None of the components are considered a reproductive hazard.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product is expected to be harmful to the aquatic environment. Releases to the environment should be avoided.

BIOACCUMULATION/ACCUMULATION: No data available

AQUATIC TOXICITY (ACUTE): Hydroquinone: 96 hr LC50 Rainbow trout: 0.638 mg/L, 48 hr EC50 Daphnia magna: 0.134 mg/L, 48 hr NOEC Daphnia magna: 0.095 mg/L, 21 day NOEC Daphnia magna: 0.0057 mg/L

COMMENTS: Persistence and Degradability: Hydroquinone: Readily biodegradable - 70% in 14 days.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: NOT REGULATED

AIR (ICAO/IATA)

SHIPPING NAME: ID8000 CONSUMER COMMODITY, 9 (PKG LESS THAN OR EQUAL TO 30 kg G); UN3334, AVIATION REGULATED LIQUID, N.O.S. (CYANOACRYLATE ESTER), 9, III, (LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0 L, OP WGT LESS THAN OR EQUAL TO 30 kg G) **

VESSEL (IMO/IMDG)

SHIPPING NAME: NOT REGULATED

COMMENTS:

* Exempt from HazMat in Non-Bulk Packaging

** This product may be shipped as EXCEPTED QUANTITIES OF CLASS 9, UN3334 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN OR EQUAL TO 1.0 L)

The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

UNITED STATES

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - ADHESIVE
 Date-Revised : 08/10/2017
 Revision No : 2

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Fire Hazard

313 REPORTABLE INGREDIENTS: None

TITLE III NOTES: Section 302 Extremely Hazardous Substances (TPQ): Hydroquinone (500 lbs).

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: This product has an RQ of 100,000 lbs (based on RQ of Hydroquinone of 100 lbs present at <0.1%). Some states have more stringent reporting requirements. Report all spills in accordance with local, state, and federal regulations.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
2-Methoxyethyl 2-cyanoacrylate	27816-23-5
Hydroquinone	123-31-9

TSCA STATUS: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

CALIFORNIA PROPOSITION 65: This product does not contain substances known to the State of California to cause cancer and/or reproductive harm.

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Department


PREPARED BY: Pacer Technology Regulatory Department Date-Revised: 08/10/2017

REVISION SUMMARY: This MSDS replaces the 08/10/2017 MSDS. Revised: Section 1: Date Issued.

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	2
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

SAFETY DATA SHEET

PACER
TECHNOLOGY
INDUSTRIAL • PRIVATE LABEL



Date Prepared : 02/27/2017
MSDS No : 90001-GHS - BATTERY
Date-Revised : 06/26/2017
Revision No : 1

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT CODE: PACER ZAP IT 4 GR (12) - BATTERY

MANUFACTURER

Pacer Technology
3281 E. Guasti Rd., Suite 260
Ontario, CA 91761

Emergency Contact: CHEMTREC

Emergency Phone: 800-424-9300

Alternate Emergency Phone: 703-527-3887

Product Stewardship: 909-987-0550

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

CONTACT WITH WATER RELEASES FLAMMABLE GASES WHICH MAY IGNITE SPONTANEOUSLY. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF SWALLOWED.

Health:

Skin Irritation, Category 1
Acute Toxicity, Category 4

Physical:

Water React., Category 1

GHS LABEL ELEMENTS

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



Flame



Corrosion

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H260: In contact with water releases flammable gases which may ignite spontaneously.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

EU014: Reacts violently with water.

PRECAUTIONARY STATEMENT(S)

Prevention:

P223: Do not allow contact with water.

P264: Wash skin and hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - BATTERY
 Date-Revised : 06/26/2017
 Revision No : 1

Response:

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P310: Immediately call a POISON CENTER or doctor/physician.

P370+P378: In case of fire: Use Lith-X powder, Class D fire extinguisher, Dry Lithium Chloride, or Graphite Powder for extinction.

Storage:

P402+P404: Store in a dry place. Store in a closed container.

Disposal:

P501: Dispose of contents through a licensed treatment, storage, disposal facility (TSDf).

HAZARDS NOT OTHERWISE CLASSIFIED: If handled properly, there are no known serious health risks. Inhalation, absorption & ingestion are unlikely under normal conditions as the battery is hermetically sealed within the device. However, if the device is crushed, or compromised in a fire, contact with the lithium metal battery and material may cause damage to eyes & skin tissue as well as the nose, throat, lungs & respiratory tract if inhaled. Please strictly observe safety instructions.

The following statements apply to the contents of the lithium metal battery if it has been compromised (e.g., opened, crushed, or punctured). These statements do not apply to the hermetically sealed device which has not been damaged or compromised.

KEEP OUT OF REACH OF CHILDREN.

IF INGESTED: Call the NATIONAL BATTERY INGESTION HOTLINE at +1 (202) 625-3333 collect, day or night.

In Canada, call +1 (416) 813-5900.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Stainless steel	71.604	
Manganese dioxide	18.192	1313-13-9
Propylene carbonate	2.047	108-32-7
1-Propene, homopolymer	1.924	9003-07-0
1,2-Dimethoxyethane	1.545	110-71-4
Lithium metal	1.224	7439-93-2
Graphite (natural)	1.114	7782-42-5
Polytetrafluoroethylene	1.114	9002-84-0
Lithium perchlorate, anhydrous	0.77	7791-03-9

4. FIRST AID MEASURES

EYES: Contents of an open battery can cause severe irritation. Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water, seek immediate medical attention.

SKIN: Contents of an open battery can cause skin irritation. Remove contaminated clothing and flush affected areas. Wash thoroughly with soap and water.

INGESTION: Swallowing a battery can be harmful. 3 volt lithium coin batteries lodged in the esophagus should be removed immediately. Leakage, chemical burns and potential perforation can occur within hours of ingestion. Seek medical attention

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - BATTERY
 Date-Revised : 06/26/2017
 Revision No : 1

immediately. **Have physician call the NATIONAL BATTERY INGESTION HOTLINE for advice and follow-up at +1 (202) 625-3333 collect day or night.**

INHALATION: Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Not anticipated under normal handling and use. If device is damaged, eye and mucous membrane irritation may occur following exposure of leaking battery.

SKIN: Not anticipated under normal handling and use. Irritation may occur following exposure to leaking battery. Symptoms of skin overexposure may include redness, itching and irritation of affected areas.

INGESTION: Not anticipated under normal handling and use. Irritation to the internal/external mouth area may occur following exposure to leaking battery.

INHALATION: Not anticipated under normal handling and use. Respiratory irritation may occur if fumes are released due to heat or an abundance of leaking batteries. Respiratory irritation, headache, irritability may occur if fumes are released due to heat or an abundance of leaking batteries.

ACUTE EFFECTS: Non-irritating when used as directed. No acute health effects reported by the manufacturer.

CHRONIC EFFECTS: Non-irritating when used as directed. No chronic health effects reported by the manufacturer.

ADDITIONAL INFORMATION: Medical Conditions Aggravated by Exposure: An initial x-ray should be obtained promptly to determine battery location. Batteries lodged in the esophagus should be removed immediately since leakage, burns, and perforation can occur as soon as 4-6 hours after ingestion.

COMMENTS: Device is hermetically sealed. Exposure to lithium battery component is not expected under normal conditions of use.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: As with any fire, wear self-contained breathing apparatus to avoid inhalation of hazardous decomposition products (See Section 2). Water will cool the fire but may react with available lithium in the batteries producing flammable hydrogen. **DO NOT RECHARGE.** As a typical sealed battery they may rupture when exposed to excessive heat. Rupture may expose lithium to moisture causing it to react or release flammable or corrosive materials. Do not accumulate undischarged batteries together. In case of fire where lithium batteries are present, flood area with water or smother with a Class D fire extinguisher appropriate for lithium metal, such as Lith-X. Virtually all fires involving lithium batteries can be controlled by flooding with water. However, the contents of the battery will react with water and form hydrogen gas. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended. A smothering agent will extinguish burning lithium batteries. Emergency Responders should wear self-contained breathing apparatus. Burning lithium manganese dioxide batteries produce toxic and corrosive lithium hydroxide fumes.

EXTINGUISHING MEDIA: Lith-X-Powder, Class D Fire Extinguisher, Dry Lithium Chloride, Graphite Powder.

Not flammable under normal conditions. However, battery will burn if involved in a fire. Call fire department. Cool exterior of battery if exposed to fire to prevent rupture. The electrolyte vapors generated by heat or fire are corrosive.

FIRE FIGHTING PROCEDURES: **DO NOT USE WATER,** moist sand, CO₂, class ABC or soda ash extinguisher. When water is used hydrogen gas may be evolved which can form an explosive mixture with air. Keep containers cool until well after fire is out, do NOT use water. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - BATTERY
 Date-Revised : 06/26/2017
 Revision No : 1

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: None under normal conditions. If the contents leak, observe the following instructions: Secure spill area and maximize ventilation. Stop spill or leak at source if safely possible. Deny entry to all unprotected individuals. Individuals involved in the cleanup must wear appropriate personal protective equipment to avoid breathing vapors or touching liquid. Recover or cover with inert absorbent material and place into appropriate container(s) for disposal. If in water remove if safe to do so. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers or any natural waterway or drinking supply. Spills are unlikely as the battery is enclosed hermetically sealed device. Keep spills and cleaning runoff out of drains, municipal sewers, and open bodies of water.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: DO NOT swallow, apply excessive force to the positive terminal, drop, weld the terminal or wire to the body of the battery directly, short-circuit the battery, charge, forcibly discharge, heat expose to open flame, disassemble, reverse the positive and negative terminals when mounting, use different batteries together, touch any liquid that leaks from the battery, or hold the battery for an extended period.

HANDLING: Keep battery away from water.

STORAGE: Never store in hot or very humid place. Storage and handling areas should be equipped with proper containment to capture and neutralize spills. Do not expose to excessive physical shock or vibration. Storage and use areas should be equipped with eyewash stations and safety showers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m ³
Manganese dioxide	ACGIH TLV	TLV		5
	OSHA PEL	PEL		5
1,2-Dimethoxyethane	ACGIH TLV	TLV	3	
Graphite (natural)	ACGIH TLV	TLV		2

ENGINEERING CONTROLS: General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station). Upon completion of work activities involving large quantities of this product (fluid), wash any exposed areas thoroughly with soap and water.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Avoid eye contact. Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash and water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).

SKIN: Use gloves constructed of chemical-resistant material such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the appropriate standards of Canada, or the EU member states. Do not wear rings, watches or jewelry that could entrap the material against the skin.

RESPIRATORY: No special respiratory protection is required under typical circumstances of use or handling. In instances

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - BATTERY
 Date-Revised : 06/26/2017
 Revision No : 1

where mist or vapors of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR 1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.

PROTECTIVE CLOTHING: No apron required when handling sealed undamaged battery. Where contact is likely corrosive-resistant apron, clothing and boots. Protective clothing, if used, should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: None for sealed device.

ODOR THRESHOLD: Not applicable

APPEARANCE: Hermetically sealed, metallic article.

pH: Not applicable

FLASHPOINT AND METHOD: Not applicable

FLAMMABLE LIMITS: Not applicable

AUTOIGNITION TEMPERATURE: Not applicable

VAPOR PRESSURE: Not applicable

VAPOR DENSITY: Not applicable

BOILING POINT: Not applicable

FREEZING POINT: Not applicable

MELTING POINT: Not applicable

THERMAL DECOMPOSITION: Not applicable

SOLUBILITY IN WATER: Insoluble

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not applicable

SPECIFIC GRAVITY: 2 to 3.0

VISCOSITY: Not applicable

10. STABILITY AND REACTIVITY

REACTIVITY: Stable under normal conditions; unstable with heat or contamination or if broken or leaking.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Prolonged overcharge; sources of ignition. Excess physical shock and vibration. Contact with organic materials, combustibles, strong reducing agents, strong oxidizers and humidity.

HAZARDOUS DECOMPOSITION PRODUCTS: Sulfur dioxide, hydrogen chloride, hydrogen.

INCOMPATIBLE MATERIALS: Contact with organic materials, strong reducing agents, strong oxidizers, water and excessive humidity.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - BATTERY
 Date-Revised : 06/26/2017
 Revision No : 1

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Manganese dioxide	> 3478 mg/kg		
Propylene carbonate	29100 uL/kg	> 20 mL/kg	> 5 g/m3

CARCINOGENICITY

NOTES: Carbon Black is listed as IARC Group 2B (Possibly carcinogenic to humans); CA65 (cancer).

REPRODUCTIVE TOXICITY: This product is not reported to produce reproductive toxicity in humans.

COMMENTS: 1,2-Dimethoxyethane: LDLO (oral, rat): 1,000 mg/kg, LCLO (inh-6h, rat):63 g/m3

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: There is no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with federal, state, provincial, and local regulations.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)**

PROPER SHIPPING NAME: UN3091, LITHIUM METAL BATTERIES CONTAINED IN EQUIPMENT, 9, II

OTHER SHIPPING INFORMATION: See 49 CFR 173.185

AIR (ICAO/IATA)

SHIPPING NAME: UN3091, LITHIUM METAL BATTERIES CONTAINED IN EQUIPMENT, 9, II

NOTE: See Section II of Packing Instruction 970

VESSEL (IMO/IMDG)

SHIPPING NAME: UN3091, LITHIUM METAL BATTERIES CONTAINED IN EQUIPMENT, 9, II

SPECIAL PROVISIONS: See IMDG Code Special Provision 188

COMMENTS: The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

313 REPORTABLE INGREDIENTS: This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA RQ: Not applicable

TSCA (TOXIC SUBSTANCE CONTROL ACT)

SAFETY DATA SHEET



Date Prepared : 02/27/2017
 MSDS No : 90001-GHS - BATTERY
 Date-Revised : 06/26/2017
 Revision No : 1

Chemical Name	CAS
Manganese dioxide	1313-13-9
Propylene carbonate	108-32-7
1-Propene, homopolymer	9003-07-0
1,2-Dimethoxyethane	110-71-4
Lithium metal	7439-93-2
Graphite (natural)	7782-42-5
Polytetrafluoroethylene	9002-84-0
Lithium perchlorate, anhydrous	7791-03-9

TSCA STATUS: The components of this product are listed on the TSCA Inventory or are otherwise exempt.

CLEAN AIR ACT (HAZARDOUS AIR POLLUTANTS): Manganese (and its compounds) is listed as a Hazardous Air Pollutant (HAP). This product does not contain any Class 1 or Class 2 ozone depleters.

REGULATIONS

STATE REGULATIONS: Note: Perchlorate Material - special handling may apply. For more information visit:
www.dtsc.ca.gov/hazardouswaste/perchlorate

CLEAN WATER ACT: Manganese (and its compounds) is listed as Toxic Pollutants under the Clean Water Act (CWA).

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): None of the components of this product are listed on the Priorities Substances list. WHMIS D2B (Other Toxic Effects)

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Department

PREPARED BY: Pacer Technology Regulatory Department **Date-Revised:** 06/26/2017

REVISION SUMMARY: This MSDS replaces the 03/28/2017 MSDS. Revised: **Section 1:** 24 HR. EMERGENCY TELEPHONE NUMBERS, MSDS No, PRODUCT CODE. **Section 3:** Wt.%. **Section 14:** AIR (ICAO/IATA) (NOTE), DOT (DEPARTMENT OF TRANSPORTATION) - OTHER SHIPPING INFORMATION VESSEL (IMO/IMDG) (SPECIAL PROVISIONS). **Section 15:** CALIFORNIA PROPOSITION 65. **Section 16:** HMIS RATING (HEALTH, PHYSICAL HAZARD, PERSONAL PROTECTION), NFPA CODES (HEALTH, REACTIVITY).

HMIS RATING

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	1
PERSONAL PROTECTION	B

NFPA CODES

